



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: B01J 19/10	A1	(11) International Publication Number: WO 00/35579 (43) International Publication Date: 22 June 2000 (22.06.00)
(21) International Application Number: PCT/GB99/03857 (22) International Filing Date: 22 November 1999 (22.11.99) (30) Priority Data: 9827360.0 12 December 1998 (12.12.98) GB (71) Applicant (for all designated States except US): AEA TECHNOLOGY PLC [GB/GB]; 329 Harwell, Didcot, Oxfordshire OX11 0RA (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): PERKINS, John, Patrick [GB/GB]; Sonic Systems, Bakers Farm Barns, Puckington, Ilminster, Somerset TA19 9JA (GB). (74) Agents: MANSFIELD, Peter, Turquand et al.; AEA Technology plc, Patents Dept., 329 Harwell, Didcot, Oxfordshire OX11 0RA (GB).	(81) Designated States: GB, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.	

(54) Title: PROCESS AND APPARATUS FOR IRRADIATING FLUIDS

(57) Abstract

Fluids in a vessel are subjected to a high ultrasonic intensity, by means of several ultrasonic transducers attached to a wall of the vessel, each transducer (14) radiating no more than 3 W/cm², the transducers being sufficiently close to each other, and the number of transducers being sufficiently high, that the power dissipation within the vessel is at least 25 W/litre. The number of transducers (14), the power of the transducers, and the volume of the vessel may be such that the power density is between 40 and 80 W/litre. The vessel may be double walled, and the space between the two walls be filled by a low attenuation buffer liquid (36) whose cavitation threshold is above that of the liquid to be treated.

